




1/2" & 3/8" Professional Air Impact Wrench



ST-55303 3/8" Dr.
Twin Dog
Torque: 108 Nm(80 ft-lb)



ST-5530 3/8" Dr.
Rocking Dog
Torque: 136 Nm(100 ft-lb)



ST-5534 3/8" Dr.
Jumbo Hammer
Torque: 271 Nm(200 ft-lb)



ST-5531 3/8" Dr.
Pin Clutch
Torque: 298 Nm(220 ft-lb)



ST-5131 3/8" Dr.
Twin Hammer
Torque: 434 Nm(320 ft-lb)
-mini type-



ST-5538 3/8" Dr.
Pin Clutch
Torque 475 Nm(350 ft-lb)



ST-5541 1/2" Dr.
Pin Clutch
Torque: 434 Nm(320 ft-lb)



ST-6643 1/2" Dr.
Pin Clutch
Torque: 515 Nm(380 ft-lb)



ST-5549A 1/2" Dr.
Pin Clutch
Torque: 542 Nm(400 ft-lb)



ST-55414 1/2" Dr.
Pin Clutch
Torque: 542 Nm(400 ft-lb)



ST-5549 1/2" Dr.
Pin Clutch
Torque: 610 Nm(450 ft-lb)



ST-5400 1/2" Dr.
Pin Clutch
Torque: 610 Nm(450 ft-lb)



ST-55449 1/2" Dr.
Pin Clutch
Torque: 676 Nm(500 ft-lb)

Specification:

Recommend Air Pressure: 6.2bar (90psi)

Model No.	Square Drive (inch)	Capacity Bolt Size		Free Speed (r.p.m.)	Max. Torque		Overall Length		Air Inlet (PT)	Air Hose (I.D.)	Air Consumption		Net Weight		Packing Pcs/Ctn/G.W./Cuft (kgs)
		inch	mm		ft-lb	N-m	in	mm			cfm	l/min	lbs	kgs	
ST-55303	3/8	3/8	M10	13,000	80	108	5-1/2	139	1/4"	3/8"	15	425	1.16	0.53	20Pcs/Ctn/18.1/0.9'
ST-5530	3/8	3/8	M10	10,000	100	136	6-1/10	155	1/4"	3/8"	15	430	1.8	0.8	20Pcs/Ctn/20/0.7'
ST-5534	3/8	7/16	M11	10,000	200	271	5-1/2	139	1/4"	3/8"	15	430	2.97	1.35	12Pcs/Ctn/19.6/1.3'
ST-5531	3/8	1/2	M13	8,500	220	298	6-1/10	155	1/4"	3/8"	15	430	2.97	1.35	10Pcs/Ctn/17/1.22'
ST-5131	3/8	5/8	M16	11,500	320	434	4-4/5	122	1/4"	3/8"	15	430	3.5	1.6	10Pcs/Ctn/13/0.8'
ST-5538	3/8	9/16	M15	10,000	350	475	6-1/7	156	1/4"	3/8"	15	430	2.68	1.22	12Pcs/Ctn/14/1.1'
ST-5541	1/2	5/8	M16	7,000	320	434	7-1/2	190	1/4"	3/8"	15	430	5.5	2.4	10Pcs/Ctn/25/1.3'
ST-6643	1/2	5/8	M16	7,000	380	515	7-1/2	190	1/4"	3/8"	15	430	5.9	2.7	8Pcs/Ctn/24/1.3'
ST-5549A	1/2	5/8	M16	7,000	400	542	7-3/4	197	1/4"	3/8"	15	430	5	2.4	10Pcs/Ctn/25/1.3'
ST-55414	1/2	5/8	M16	8,000	400	542	7-1/2	190	1/4"	3/8"	15	430	4.4	2	10Pcs/Ctn/21/1.2'
ST-5549	1/2	5/8	M16	7,000	450	610	7-1/2	190	1/4"	3/8"	15	430	5.3	2.4	10Pcs/Ctn/25/1.3'
ST-5400	1/2	3/4	M18	7,000	450	610	7-7/8	198	1/4"	3/8"	15	430	5.9	2.68	8Pcs/Ctn/24/1.28'
ST-55449	1/2	5/8	M16	7,000	500	676	7-4/5	197	1/4"	3/8"	15	430	5.7	2.5	10Pcs/Ctn/25/1.5'