

## WEP 15-125 Quick (600476000) Angle Grinder

(220-240 V / 50 - 60 Hz); Cardboard box

Order no. 600476000 EAN 4007430245618



Product may differ from Image













- Highest service life for extreme applications: robust, powerful angle grinder with greatest power density in its class for quick work progress
- New, patent-pending Metabo Marathon motor with up to 50% more torque and up to 20% higher overload capacity for quicker material removal and longer service life
- Tacho-Constamatic (TC)-Full Wave Electronics: fast work progress by means of constant speed under load
- Now even faster: M-Quick System for tool-free disc change at the touch of a button by means of M-Quick flange nut
- Tool-free adjustable guard; twist-proof
- Metabo VibraTech (MVT) side handle for vibration damping for convenient continuous operation
- Paddle switch with dead-man function: safe to operate due to an ergonomically integrated non-slip switch
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly
  for maximum user protection and swift progress
- Electronic overload protection, soft start and restart protection
- Gear housing can be mounted when rotated in 90° steps for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

Technical data	
Characteristics	
Grinding Disc Ø	125 mm / 5 "
Rated Input Power	1550 W
Output Power	940 W
No-Load Speed	11000 /min
Revolutions at Rated Load	11000 /min
Torque	3.5 Nm / 31 in-lbs
Spindle Thread	M 14
Weight (without power cable)	2.5 kg / 5.5 lbs
Cable Length	4 m / 13 ft

www.metabo.com 1/2



## Vibration

Surface grinding	6 m/s <sup>2</sup>	
Uncertainty of measurement K	1.5 m/s²	
Grinding with sandpaper	3.6 m/s²	
Uncertainty of measurement K	1.5 m/s <sup>2</sup>	
Noise emission		
Sound Pressure Level	93 dB(A)	
Sound power lev el (LwA)	104 dB(A)	
Uncertainty of measurement K	3 dB(A)	

## Scope of delivery

Guard

Inner support flange

M-Quick flange nut

Metabo VibraTech (MVT) side handle

www.metabo.com 2/2