



Air Screwdriver



ST-4480
Torque: 3.7~9.6 ft/lb (5-13Nm)
ST-4481
Torque: 3.7~11.8 ft/lb (5-16Nm)
Air Adjustable Clutch Screwdriver



ST-4488
Torque: 3.76~12.1 ft/lb (5.1-16.4Nm)
ST-4489
Torque: 3.76~12.1 ft/lb (5.1-16.4Nm)
Air External Adjustable Screwdriver



ST-4486
Torque: 2.5~5.8 ft/lb (3.4-7.9Nm)
ST-4487
Torque: 2.5~7.9 ft/lb (3.4-10.7Nm)
Air Adjustable Clutch Screwdriver



ST-4468
Air Impact Screwdriver
(Double Hammer)



ST-4469
Heavy Duty Air Impact
Screwdriver
(Double Hammer)



ST-55303S
1/4" HEX Super Duty Air Mini
Impact Screwdriver (Twin Dog)
Max Torque: 95 Nm (70 ft-lb)



ST-4450
Air Adjustable
Clutch Screwdriver



ST-4460
Air Impact Screwdriver
(Double Hammer)



ST-4474B
Air Shut-off Screwdriver
(Push to Start)

ST-4460AK
10 Pcs Air Impact Screwdriver Kit
Contents:
1- ST-4460A
1- Slotted Bits 5mmx50m/m
2- Slotted Bits 6mmx50m/m
1- Phillips Bits No.1x65m/m
2- Phillips Bits No.2x65m/m
1- Phillips Bits No.2x100m/m
1- Plug
1- Blow Case



ST-4450A
Air Adjustable Clutch
Screwdriver W/Quick
Change Chuck



ST-4460A
Air Impact Screwdriver
W/Quick Change Chuck
(Double Hammer)



ST-4470A
Heavy Duty Air Impact
Screwdriver
(Double Hammer)

ST-4468K
9 Pcs Air Impact Screwdriver Kit
(Double Hammer)
Contents:
1- ST-4468
2- Slotted Bits 6mmx50m/m
2- Phillips Bits No.2x65m/m
1- Phillips Bits No.2x100m/m
1- Plug
1- Oil pot
1- Blow Case



Specification:

Recommend Air Pressure: 6.2bar (90psi)

Model No.	Hex Shank Size		Free Speed (r.p.m.)	Max. Torque		Overall Length		Air Inlet (PT)	Air Hose (I.D.)	Air Consumption		Net Weight		Packing Pcs/Ctn/G.W./Cuft (kgs)
	inch	mm		ft-lb	N-m	in	mm			cfm	l/min	lbs	kgs	
ST-4480	1/4	6.35	1,800	3.7-9.6	5-13	7	180	1/4"	3/8"	16	450	2.5	1.14	10/Ctn/15'1"
ST-4481	1/4	6.35	800	3.7-11.8	5-16	8-1/2	216	1/4"	3/8"	16	450	2.7	1.21	10/Ctn/17'0.93'
ST-4488	1/4	6.35	1,800	3.76-12.1	5.1-16.4	9	230	1/4"	3/8"	16	450	3	1.36	10/Ctn/17.5/1.44'
ST-4489	1/4	6.35	800	3.76-12.1	5.1-16.4	10	256	1/4"	3/8"	16	450	3.3	1.5	10/Ctn/16/1.1'
ST-4486	1/4	6.35	1,800	2.5-5.8	3.4-7.9	7	180	1/4"	3/8"	16	450	2.5	1.14	10/Ctn/14/0.96'
ST-4487	1/4	6.35	800	2.5-7.9	3.4-10.7	8-1/2	216	1/4"	3/8"	16	450	2.7	1.21	10/Ctn/16/0.91'
ST-4468	1/4	6.35	13,000	26	35	5-3/5	143	1/4"	3/8"	9.5	270	1.9	0.88	20/Ctn/12/1.1'
ST-4469	1/4	6.35	7,500	148	200	9	230	1/4"	3/8"	9.5	270	2.4	1.12	20/Ctn/15/1.1'
ST-4450	1/4	6.35	1,700	2.2	3	9-1/4	235	1/4"	3/8"	9.5	270	1.4	0.65	20/Ctn/17/1.1'
ST-4460	1/4	6.35	12,000	26	35	7	178	1/4"	3/8"	9.5	270	1.5	0.7	20/Ctn/16/1.1'
ST-4474B	1/4	6.35	800	0.26-0.7	0.35-1.0	7-1/2	190	1/4"	3/8"	9.5	270	0.81	0.37	10/Ctn/7/0.9'
ST-4450A	1/4	6.35	1,700	2.2	3	9-1/4	235	1/4"	3/8"	9.5	270	1.4	0.66	20/Ctn/17/1.1'
ST-4460A	1/4	6.35	12,000	26	35	7-7/25	185	1/4"	3/8"	9.5	270	1.5	0.7	20/Ctn/17/1.1'
ST-4470A	1/4	6.35	8,000	148	200	8-23/26	225	1/4"	3/8"	9.5	270	2.4	1.1	10/Ctn/13/0.9'
ST-55303S	1/4	6.35	12,000	70	95	5-12/25	146.4	1/4"	3/8"	15	425	1.2	0.55	20/Ctn/18.1/0.9'