



# Air Screwdriver



**ST-4480**  
Torque: 3.7~9.6 ft/lb (5-13Nm)  
**ST-4481**  
Torque: 3.7~11.8 ft/lb (5-16Nm)  
Air Adjustable Clutch Screwdriver



**ST-4488**  
Torque: 3.76~12.1 ft/lb (5.1-16.4Nm)  
**ST-4489**  
Torque: 3.76~12.1 ft/lb (5.1-16.4Nm)  
Air External Adjustable Screwdriver



**ST-4486**  
Torque: 2.5~5.8 ft/lb (3.4-7.9Nm)  
**ST-4487**  
Torque: 2.5~7.9 ft/lb (3.4-10.7Nm)  
Air Adjustable Clutch Screwdriver



**ST-4468**  
Air Impact Screwdriver  
(Double Hammer)



**ST-4469**  
Heavy Duty Air Impact  
Screwdriver  
(Double Hammer)



**ST-55303S**  
1/4" HEX Super Duty Air Mini  
Impact Screwdriver (Twin Dog)  
Max Torque: 95 Nm (70 ft-lb)



**ST-4450**  
Air Adjustable  
Clutch Screwdriver



**ST-4460**  
Air Impact Screwdriver  
(Double Hammer)



**ST-4474B**  
Air Shut-off Screwdriver  
(Push to Start)

**ST-4460AK**  
10 Pcs Air Impact Screwdriver Kit  
Contents:  
1- ST-4460A  
1- Slotted Bits 5mmx50m/m  
2- Slotted Bits 6mmx50m/m  
1- Phillips Bits No.1x65m/m  
2- Phillips Bits No.2x65m/m  
1- Phillips Bits No.2x100m/m  
1- Plug  
1- Blow Case



**ST-4450A**  
Air Adjustable Clutch  
Screwdriver W/Quick  
Change Chuck



**ST-4460A**  
Air Impact Screwdriver  
W/Quick Change Chuck  
(Double Hammer)



**ST-4470A**  
Heavy Duty Air Impact  
Screwdriver  
(Double Hammer)

**ST-4468K**  
9 Pcs Air Impact Screwdriver Kit  
(Double Hammer)  
Contents:  
1- ST-4468  
2- Slotted Bits 6mmx50m/m  
2- Phillips Bits No.2x65m/m  
1- Phillips Bits No.2x100m/m  
1- Plug  
1- Oil pot  
1- Blow Case



## Specification:

Recommend Air Pressure: 6.2bar (90psi)

Model No.	Hex Shank Size		Free Speed (r.p.m.)	Max. Torque		Overall Length		Air Inlet (PT)	Air Hose (I.D.)	Air Consumption		Net Weight		Packing Pcs/Ctn/G.W./Cuft (kgs)
	inch	mm		ft-lb	N-m	in	mm			cfm	l/min	lbs	kgs	
ST-4480	1/4	6.35	1,800	3.7-9.6	5-13	7	180	1/4"	3/8"	16	450	2.5	1.14	10/Ctn/15/1'
ST-4481	1/4	6.35	800	3.7-11.8	5-16	8-1/2	216	1/4"	3/8"	16	450	2.7	1.21	10/Ctn/17/0.93'
ST-4488	1/4	6.35	1,800	3.76-12.1	5.1-16.4	9	230	1/4"	3/8"	16	450	3	1.36	10/Ctn/17.5/1.44'
ST-4489	1/4	6.35	800	3.76-12.1	5.1-16.4	10	256	1/4"	3/8"	16	450	3.3	1.5	10/Ctn/16/1.1'
ST-4486	1/4	6.35	1,800	2.5-5.8	3.4-7.9	7	180	1/4"	3/8"	16	450	2.5	1.14	10/Ctn/14/0.96'
ST-4487	1/4	6.35	800	2.5-7.9	3.4-10.7	8-1/2	216	1/4"	3/8"	16	450	2.7	1.21	10/Ctn/16/0.91'
ST-4468	1/4	6.35	13,000	26	35	5-3/5	143	1/4"	3/8"	9.5	270	1.9	0.88	20/Ctn/12/1.1'
ST-4469	1/4	6.35	7,500	148	200	9	230	1/4"	3/8"	9.5	270	2.4	1.12	20/Ctn/15/1.1'
ST-4450	1/4	6.35	1,700	2.2	3	9-1/4	235	1/4"	3/8"	9.5	270	1.4	0.65	20/Ctn/17/1.1'
ST-4460	1/4	6.35	12,000	26	35	7	178	1/4"	3/8"	9.5	270	1.5	0.7	20/Ctn/16/1.1'
ST-4474B	1/4	6.35	800	0.26-0.7	0.35-1.0	7-1/2	190	1/4"	3/8"	9.5	270	0.81	0.37	10/Ctn/7/0.9'
ST-4450A	1/4	6.35	1,700	2.2	3	9-1/4	235	1/4"	3/8"	9.5	270	1.4	0.66	20/Ctn/17/1.1'
ST-4460A	1/4	6.35	12,000	26	35	7-7/25	185	1/4"	3/8"	9.5	270	1.5	0.7	20/Ctn/17/1.1'
ST-4470A	1/4	6.35	8,000	148	200	8-23/26	225	1/4"	3/8"	9.5	270	2.4	1.1	10/Ctn/13/0.9'
ST-55303S	1/4	6.35	12,000	70	95	5-12/25	146.4	1/4"	3/8"	15	425	1.2	0.55	20/Ctn/18.1/0.9'