



3/8" Air Drill

LOW NOISE



ST-4232C
3/8" Heavy Duty Air Drill
W/Keyless Chuck
Noise:87dB(A) (0.9HP)
Speed: 1,800 rpm

Option:High Speed Type

ST-4232H(C)-26 2,600rpm
ST-4232H(C)-32 3,200rpm
ST-4232H(C)-45 4,500rpm



ST-4232

LOW NOISE



ST-4233C
3/8" Heavy Duty
Reversible Air Drill
W/Keyless Chuck
Noise:87dB(A) (0.9HP)
Speed: 1,600 rpm

Option:High Speed Type

ST-4233H(C)-20 2,000rpm
ST-4233H(C)-26 2,600rpm



ST-4233



4431-02
3/8" Key Chuck
(3/8"x24)



4431-02C
3/8" Keyless Chuck
(3/8"x24)

ST-4430
3/8" Air Drill
Speed: 2,200 rpm



ST-4430C
3/8" Air Drill
W/Keyless Chuck
Speed: 2,200 rpm

ST-4131
3/8" Reversible Air Drill
Speed: 1,800 rpm



ST-4431
3/8" Air Reversible Drill
Speed: 1,800 rpm



ST-4431C
3/8" Reversible Air Drill
W/Keyless Chuck
Speed: 1,800 rpm

ST-4434A
3/8" Heavy Duty Reversible Air Drill
Speed: 1,800 rpm



ST-4434AC
3/8" Heavy Duty Reversible Air Drill
W/Keyless Chuck
Speed: 1,800 rpm

Specification:

Recommend Air Pressure: 6.2bar (90psi)

Model No.	Drilling Cap		Free Speed (r.p.m.)	Overall Length		Air Inlet (PT)	Air Hose (I.D.)	Air Consumption		Net Weight		Packing Pcs/Ctn/G.W./Cutt (kgs)
	in	mm		in	mm			cfm	l/min	lbs	kgs	
ST-4232(C)	3/8	10	1,800	8.7	220	1/4"	3/8"	14	396	2.7	1.22	10Pcs/Ctn/14/0.8'
ST-4233(C)	3/8	10	1,600	8.7	220	1/4"	3/8"	14	396	2.8	1.25	10Pcs/Ctn/14/0.8'
ST-4430(C)	3/8	10	2,200	7	180	1/4"	3/8"	14	396	2.0	0.9	10Pcs/Ctn/14/0.8'
ST-4131	3/8	10	1,800	7	180	1/4"	3/8"	14	396	2.0	0.9	10Pcs/Ctn/15.5/1'
ST-4431(C)	3/8	10	1,800	7	180	1/4"	3/8"	14	396	2.0	0.9	10Pcs/Ctn/14/0.8'
ST-4434A(C)	3/8	10	1,800	7	180	1/4"	3/8"	14	396	3.0	1.4	10Pcs/Ctn/14/1'

*Model with "C" at the end is keyless chuck.